DATA SHEET

10X20FT



10X20FT CANOPY TENT

Equip your commercial-grade Ecotent with your option of tent fabrics and customization options. Your Ecotent Product Expert can assist with any questions, pricing, and product support.

15.7 x 27.6 x 60"

OUICK LINKS:

Ecotent Website 3D Tent Configurator

Tent Sizes Photo Gallery

Technical Details Warranties & Certificates



| TECHNICAL DETAILS | E1* | E2" | E3. |
|---|---|---|--|
| Frame Construction | | | |
| Frame Material Leg Shape Leg Profile Truss Profile Connecting Elements Footplate Material Push-Button Locks Corner Brackets | All-Aluminum Ribbed Square 46x56.5mm (2.5mm) 30x15mm (2.8mm) Aluminum, Rubber Cover Anodized Aluminum Comfort Press Fixed Position | Aluminum & Nylon Ribbed Square 43x55.5mm (2.5mm) 28.5x15mm (2mm) Fiber Reinforced Nylon Anodized Aluminum Comfort Press | Aluminum & Nylon Ribbed Square 32x41mm (2.1mm) 28.5x15mm (2mm) Fiber Reinforced Nylon Galvanized Steel Comfort Press X |
| Weight | 121.9lb (55.4kg) | 108.5lb (49.3kg) | 88.4lb (40.2kg) |
| Transport Bag | ✓ Heavy-Duty PVC | ✓ Heavy-Duty PVC | ✓ Standard Poly |
| Frame Height Extensions | ✓ Up to 36" | ✓ Up to 12" | × |

| TEXTILE PROPERTIES | OXFORD 500D | OXFORD 250D |
|---|--|-------------------------------------|
| Waterproof Rating (DIN EN 20811) | ✓ 2x Industry Avg. 2,000mm | ✓ 1.5x Industry Avg. 1,600mm |
| Fire Certifications B - s1, d0 (difficult to ignite) | NFPA 701, CPAI-84 Se CAN/ULC-S109, CA Tit | |
| Color Fade Resistance (DIN EN ISO 105-B02) | Durable blue scale: 4.5-6.5 of 8 | Durable blue scale: 4.5-6.5 of 8 |
| Printing Options | ✓ Thermal & Full | ✓ Thermal & Full |

*NFR: Non-Fire Rated. All fabrics are certified fire-retardent unless labeled as NFR.

FABRIC COLORS



Roof Textile Options

Oxford 500D, Oxford 250D, Oxford 250D NFR*, PVC & Recycled Fabric NFR*